

DAVE SAYS

When lowering a pump into the water ALWAYS use the handle or a rope tied to the handle - NEVER use the power lead - as this risks pulling the mains lead out of the pump.



1 SWP120 120L/min (max.) 200W 230V Submersible Water Pump

DIY/domestic use in and around the home and garden. Ideal for irrigating gardens, draining cellars/basements and powering waterfalls/fountains. Pump has a ceramic shaft for long life and has thermal overload protection. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) of cable. Display carton. Specification:

Maximum head height	... 6M
Maximum output	... 120L/min
Hose Height - Approx. Output	... 1.5M - 80L/min 3.0M - 55L/min 5.0M - 25L/min
Maximum water temperature	... 35°C
Maximum particle size	... 4mm dia.
Output aperture	... 25mm dia.

Stock No.	Box Qty	Price each
35463	-	£59.92P



3 SWP120ASS 120L/min (max.) 200W 230V Stainless Steel Body Submersible Water Pump with Float Switch

DIY/domestic use in and around the home and garden. Ideal for irrigating gardens, draining cellars/basements and powering waterfalls/fountains. Ceramic shaft for long life, thermal overload protection and float switch which automatically cuts pump off when water level has dropped. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) cable. Display carton. Specification:

Maximum head height	... 6M
Maximum output	... 120L/min
Hose Height - Approx. Output	... 1.5M - 80L/min 3.0M - 55L/min 5.0M - 25L/min
Maximum water temperature	... 35°C
Maximum particle size	... 4mm dia.
Output aperture	... 25mm dia.

Stock No.	Box Qty	Price each
64275	-	£85.06P



5 SWP125ADW 125L/min (max.) 400W 230V Submersible Dirty Water Pump with Float Switch

Ideal for pumping out inspection pits, ditches and footings where suspended solids may be present, general irrigation and other similar applications. Ceramic shaft for long life, thermal overload protection and float switch which automatically turns pump off when water level has dropped. Supplied complete with 10M (approx.) cable and BS approved non-rewireable moulded plug and cable. Display carton. Specification:

Maximum head height	... 5M
Maximum output	... 125L/min
Maximum water temperature	... 35°C
Maximum particle size	... 30mm dia.
Output aperture	... 32mm dia.

Stock No.	Box Qty	Price each
76334	-	£56.50P



2 SWP120A 120L/min (max.) 200W Submersible Water Pumps with Float Switch

DIY/domestic use in and around the home and garden. Ideal for irrigating gardens, draining cellars/basements and powering waterfalls/fountains. Ceramic shaft for long life, thermal overload protection and float switch which automatically cuts pump off when water level has dropped. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) cable. (230V AC only). Display carton. Specification:

Maximum head height	... 6M
Maximum output	... 120L/min
Hose Height - Approx. Output	... 1.5M - 80L/min 3.0M - 55L/min 5.0M - 25L/min
Maximum water temperature	... 35°C
Maximum particle size	... 4mm dia.
Output aperture	... 25mm dia.

Stock No.	Voltage	Box Qty	Price each
52064	110V	-	£84.00P
35464	230V	-	£61.96P



4 SWP125IFS 120L/min (Max.) 230V Submersible Water Pump with Integral Float Switch

For general usage around the home and garden. Ideal for irrigating gardens, draining cellars/basements, tight boreholes and powering waterfalls/fountains. Ceramic shaft for long life, thermal overload protection and integral float switch which automatically cuts pump off when water level has dropped. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) cable. Display carton. Specification:

Maximum head height	... 6.5M
Maximum output	... 120L/min
Hose Height - Approx. Output	... 3M - 100L/min 4M - 80L/min 6M - 30L/min
Maximum water temperature	... 35°C
Maximum particle size	... 5mm dia.
Motor	... 300W
Output aperture	... 32mm dia.

Stock No.	Box Qty	Price each
87961	-	£85.06P



6 SWP144A 144L/min (max.) 350W 230V Submersible Water Pump with Float Switch

For general usage around the home and garden. Ideal for irrigating gardens, draining cellars/basements and powering waterfalls/fountains. Ceramic shaft for long life, thermal overload protection and float switch which automatically cuts pump off when water level has dropped. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) cable. Display carton. Specification:

Maximum head height	... 7M
Maximum output	... 144L/min
Hose Height - Approx. Output	... 3M - 110L/min 4M - 55L/min 6M - 20L/min
Maximum water temperature	... 35°C
Maximum particle size	... 4mm dia.
Output aperture	... 25mm dia.

Stock No.	Box Qty	Price each
35465	-	£66.16P