



**INTEGRAL
FLOAT
SWITCH**

1 SWP195IFS
195L/min (max.) 600W 230V Submersible Water Pump with Integral Float Switch

For general usage around the home and garden. Ideal for irrigating gardens, draining cellars/basements, tight boreholes and powering waterfalls/fountains. Ceramic shaft for long life, thermal overload protection and integral float switch which automatically cuts pump off when water level has dropped. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) cable. Display carton.

Specification:

Maximum head height	... 9M
Maximum output	... 195L/min
Hose Height - Approx. Output	... 3M - 165L/min
	4M - 150L/min
	6M - 120L/min
Maximum water temperature	... 35°C
Maximum particle size	... 5mm dia.
Output aperture	... 32mm dia.

Stock No.	Box Qty	Price each
87962	-	£96.60P



3 SWP220A
220L/min (max.) 750W 230V Submersible Water Pump with Float Switch

For general usage around the home and garden. Ideal for irrigating gardens, draining cellars/basements and powering waterfalls/fountains. Ceramic shaft for long life, thermal overload protection and float switch which automatically cuts pump off when water level has dropped. Supplied complete with 19mm diameter hose adaptor, BS approved non-rewireable moulded plug and 10M (approx.) cable. Display carton.

Specification:

Maximum head height	... 10M
Maximum output	... 220L/min
Maximum water temperature	... 35°C
Maximum particle size	... 5mm dia.
Output aperture	... 32mm dia.

Stock No.	Box Qty	Price each
76333	-	£66.82P



5 SWP235ADWSS
235L/min (max.) 700W 230V Stainless Steel Body Submersible Dirty Water Pump with Float Switch

For pumping out inspection pits, ditches and footings where solids may be present; general irrigation and other heavy duty applications. Ceramic shaft for long life, thermal overload protection and float switch which automatically turns pump off when water level has dropped. Supplied complete cable with BS approved non-rewireable moulded plug and 10M (approx.) cable. Display carton.

Specification:

Maximum head height	... 8.5M
Maximum output	... 235L/min
Hose Height - Approx. Output	... 3.0M - 200L/min
	6.0M - 150L/min
	8.5M - 50L/min
Maximum water temperature	... 35°C
Maximum particle size	... 30mm dia.
Output aperture	... 32mm dia.

Stock No.	Box Qty	Price each
64274	-	£132.24P



2 SWP210ADW
210L/min (max.) 750W 230V Submersible Dirty Water Pump with Float Switch

Ideal for pumping out inspection pits, ditches and footings where suspended solids may be present, general irrigation and other similar applications. Ceramic shaft for long life, thermal overload protection and float switch which automatically turns pump off when water level has dropped. Supplied complete with 10M (approx.) cable and BS approved non-rewireable moulded plug and cable. Display carton.

Specification:

Maximum head height	... 8M
Maximum output	... 210L/min
Maximum water temperature	... 35°C
Maximum particle size	... 30mm dia.
Output aperture	... 32mm dia.

Stock No.	Box Qty	Price each
76335	-	£66.82P



4 SWP235ADW
235L/min (max.) 700W Submersible Dirty Water Pumps with Float Switch

For pumping out inspection pits, ditches and footings where solids may be present, general irrigation and other heavy duty applications. Ceramic shaft for long life, thermal overload protection and float switch which automatically turns pump off when water level has dropped. Supplied complete with BS approved non-rewireable moulded plug and 10M (approx.) cable. (230V AC only). Display carton. Specification:

Maximum head height	... 8.5M
Maximum output	... 235L/min
Hose Height - Approx. Output	... 2M - 185L/min
	4M - 150L/min
	6M - 100L/min
Maximum water temperature	... 35°C
Maximum particle size	... 30mm dia.
Output aperture	... 32mm dia.

Stock No.	Voltage	Box Qty	Price each
52066	110V	-	£128.10P
35467	230V	-	£103.96P



6 SWP320ADW
320L/min (max.) 1000W 230V Submersible Dirty Water Pump with Float Switch

For heavy duty applications such as, pumping out inspection pits, ditches and footings where solids may be present as well as general irrigation. Ceramic shaft for long life, thermal overload protection and float switch which automatically turns the pump off when water level has dropped. Supplied complete with 10M (approx.) cable with BS approved non-rewireable moulded plug and cable. Display carton.

Specification:

Maximum head height	... 11M
Maximum output	... 320L/min
Maximum particle size	... 38mm dia.
Output aperture	... 38mm dia.

Stock No.	Box Qty	Price each
69690	-	£153.30P

Important Box Qty info: For your convenience we recommend ordering in box quantity or multiples of box quantity where shown. **You can still order in any quantity** unless specifically stated otherwise.